HITACHI

Reliable Solutions

ZAXIS95 RANGE



HYDRAULIC EXCAVATOR

Model code : ZX95US-7 Nominal power : 50.4 kW

Operating weight : Mono boom : $8\,320-9\,370\,kg$ /

2 Piece boom : 9 310 - 9 440 kg

Bucket ISO heaped: 0.28 m³

Model code : ZX95US-7 SLF Nominal power : 50.4 kW

Operating weight : 9040 - 9520 kg

Bucket ISO heaped: 0.13 m³

Model code : ZX95USB-7 Nominal power : 50.4 kW

Operating weight: Mono boom: 8 760 – 9 810 kg/

2 Piece boom : 9 150 - 10 200 kg

Bucket ISO heaped: 0.28 m³

You're in control

You're at the heart of the design for our latest range of excavators. To continuously improve on previous generation machines we've focused on enhancing your experience in the cab as an operator.

We've considered the challenges you face as the owner of a successful business. And we've zoomed in on the ways in which we can support you over the life cycle of your machine.


By putting you at the heart of the Zaxis-7 range, we invite you to take control – over your workspace and your fleet.

And by working in partnership, we will help you to create your vision.

Scan the QR code to view the product film of the ZX95US/USB-7 and discover their capabilities







Inside



In control of your business

8. Improve your profit



In control of your comfort

10. Feel the difference



In control of your environment

12. Increase your safety



In control of your assets

14. Boost your uptime



In control of your fleet

16. Manage your machine



In control of your uptime

18. Protect your investment




In control of your performance

20. Get more from your machine

Complete control

put you firmly in control, so you can feel assured of your machine's performance, and supported by the technological expertise and services that Hitachi provides.





Sensors monitor oil continuously and contribute to preventative maintenance, helping to reduce downtime.



ConSite Pocket app allows you to manage and monitor your fleet remotely.



Options such as Hitachi ground engaging tools enable you to enhance the performance of your



The spacious cab

environment.

interior provides a more

comfortable working

Improved access to components ensures maintenance is quick and easy.





Integrated console and seat suspension gives a greater sense of control, and helps to reduce fatigue.



Visibility of the job site is excellent thanks to the Aerial Angle camera system and new LCD monitor.



Powerful Stage V-compliant engine does not need an SCR system, reducing life-cycle





The short turning radius and short distance between the bucket and blade make it ideal for confined spaces.



The ECO gauge on

how to lower fuel

consumption and reduce costs.

the monitor indicates

4 | ZX95US excavators



Control zone

Enhanced comfort and safety features are at your fingertips in the refined cab of Zaxis-7 excavators, giving you the power to perform productively, with ease and reduced fatigue.

- 1 Increased sweeping area of parallel link wiper enhances visibility in difficult working conditions.
- Air conditioning and audio are easily controlled via the
- 3 Low-reflective colour 8" LCD monitor is easy to view and navigate.
- (4) USB socket and smartphone holder helps you stay
- (5) Drinks holder is easy to detach for cleaning.
- Blade lever to adjust speed and angle quickly and easily.
- Ergonomically designed controls are responsive and user-friendly, preventing fatigue.

- 8 Bluetooth® for hands-free calls and DAB+ radio for music while you work.
- (9) Multifunctional control panel makes operation easier.
- 10 Improved sound isolation makes this one of the quietest cabs in the market.
- (11) Adjustable armrest both angle and height are manually adjustable and coat hooks take care of personal belongings.
- (12) Integrated console and seat suspension gives a greater sense of control and helps to reduce fatigue.
- (13) Increased legroom creates a more spacious cab.
- (14) Optimal pedal layout helps to reduce fatigue.



Operation is easy with ergonomically designed controls and switches.



Bluetooth® connection for hands-free calls while you work.

In control of your business



Improve your profit

The success of your business depends on the reliability and efficiency of your construction machinery. With Zaxis-7 compact excavators, you can count on the highest quality, the ultimate in operating comfort and reduced running costs – all of which will have a positive impact on your bottom line.

You can look forward to increasing your profits thanks to the powerful performance of the new Zaxis-7 machines. Larger than the previous generation ZX85-6, they offer 10% greater stability and 4% greater digging force, boosting productivity.

Life-cycle costs are reduced with the new Stage V-compliant engine, which does not require an SCR system. This eliminates the need for urea, filter replacements and associated maintenance, saving you time and money. Your operators can also control fuel efficiency – and reduce costs – by using the all-new ECO gauge. This is clearly visible on the multifunctional colour LCD eight-inch monitor.

In addition, you can boost your profits by working on a wider range of projects thanks to their excellent versatility. Different attachments are quickly changed using the enhanced attachment support system on the monitor, and the factory-ready quick hitch system including piping. Choose from a variety of specifications to suit any job site, including mono and two-piece boom.


Your operators can work safely in confined areas thanks to the compact size, short turning radius and shorter distance between the bucket and blade. Grading and levelling are completed quickly and easily using the optional floating angle blade. And adjusting the blade angle left or right by up to 25 degrees increases precision and efficiency.



Short distance between the bucket and blade enhances efficiency and safety.



The optional floating angle blade is ideal for grading and levelling.



The ECO gauge helps to deliver better fuel consumption.



Increased lifting capacity enables greater versatility.

8 ZX95US excavators





You're in control with a spacious, tidy and enjoyable working environment.



The cab is easy to access thanks to lower entry level and wide entrance.



The LCD monitor is easy to view with hi-res anti-glare screen.



Ergonomic multifunctional control panel provides easy access.

Feel the difference

The redesigned, state-of-the-art Zaxis-7 excavator cab gives you the perfect working environment. The ultra-spacious ZX95US-7 and ZX95USB-7 offer you an industry-leading, first-class cab with the ultimate in comfort and quality, as well as some of the lowest noise levels in the market.

Feel the difference with the synchronised motion of the seat and console, designed to ensure you feel less tired at the end of the working day. Stretch out in the most spacious Hitachi Construction Machinery cab yet, with improved pedal layout and ample legroom. And sit comfortably thanks to the easily adjustable console height with three positions to choose from.

Easy operation comes from the new ergonomic design of the console and switches, and convenient access to controls. You can navigate quickly through the menu on the 8" LCD monitor with the multifunctional controller. The hi-res anti-glare screen is also easier to view, and the refreshed layout offers a clear display and desirable functionality – such as air conditioning, DAB+ radio and Bluetooth®.

With more storage for your personal belongings, such as your coat, smartphone and drink, you'll feel instantly relaxed and ready for your shift. Added practical functions to the joysticks, such as wiper, engine idle and audio mute controls, will make your working day effortless and enjoyable.

10 ZX95US excavators | 11

In control of your environment



Increase your safety

Your ability to work safely is vital, not only for your own wellbeing, but also for the successful completion of any project. To protect yourself and your machine from potential hazards, the new Zaxis-7 excavators give you a superior view of your surroundings, so you can see the job site from all angles.

The visibility you enjoy from the cab includes an exceptional 270-degree bird's-eye view with the Aerial Angle camera system. You can choose from five image options to view the machine's immediate environment, which enables you to control your own safety – as well as that of those around you.

To help you to work more confidently and efficiently, even in the most challenging of conditions, Zaxis-7 excavators are fitted with some impressive new features. From the optional ambient light that makes the camera easier to view, to the repositioning of the lights on the boom and cab to illuminate the job site more effectively, you'll have the visibility you need when it matters most.





The fuel tank has also been repositioned to make it easier and safer to refill.



Choose between different image layouts to suit your working environment.





Relocated boom and cab lights improve visibility in challenging conditions.

12 | ZX95US excavators | 1




Convenience access to all filters in one compartment.



The battery is easy to replace.



The radiator is easily accessible for cleaning.



Designed for durability and easy maintenance, Zaxis-7 excavators increase uptime and reduce the total cost of ownership.

Boost your uptime

Completing a project on time and on budget depends on the ability of your construction equipment to perform all day, every day. That's why Hitachi Construction Machinery owners have profited from generations of ultra-reliable and durable machinery – and the Zaxis-7 range is no exception.

The latest excavators have been built to last, so that you can remain in complete control of your assets. They have been tested rigorously and continuously at dedicated facilities in Japan with the goal of significantly boosting your uptime.

Downtime is minimised by the priority given to easy maintenance and cleaning – saving you time and money. The spacious engine compartment makes it easy to carry out servicing and maintenance, the radiator is easily accessible, and the battery is easy to replace. All filters are conveniently available in one compartment for quick and easy replacement.



Manage your machine

Hitachi Construction Machinery offers a wide range of after-sales services to help you feel in total control of your fleet and workload. These initiatives give you access to vital data and tools to manage your machine.

Remote monitoring systems Owner's Site and ConSite send operational data daily via GPRS or satellite from your excavator to www.globaleservice.com. This includes: ratios of operating hours to enhance efficiency; fuel consumption to manage running costs; and machine location for planning purposes. ConSite summarises the information in a monthly email.

The ConSite Pocket App sends you real-time alerts for issues arising with your machine. You'll receive recommendations on what to do and step-by-step help guides. The app also enables you to see the location of your fleet.

A unique innovation continuously monitors the quality of engine and hydraulic oil, 24/7. Data is transmitted daily via two oil sensors to Global e-Service. These detect if the oil quality has deteriorated, due to contamination or low viscosity. If this happens, you and your authorised Hitachi Construction Machinery dealer will receive an alert.


This innovative feature provides accurate estimations of when oil changes are required. It reduces maintenance and unscheduled downtime, and gives you peace of mind thanks to scheduled servicing and ultimately a higher resale value.



The unique oil sensor reduces maintenance and downtime.



A wide range of data on Global e-Service enhances efficiency.



The alerts on the ConSite Pocket App provide real-time information.



Hitachi offers a wide range of after-sales services for planning maintenance and managing running costs.

16 ZX95US excavators






Minimise downtime with Hitachi Construction Machinery Genuine Parts.



HELP extended warranties and service contracts provide optimal performance.



Hitachi Construction Machinery Premium Rental enables you to pay as you earn.



Hitachi Construction Machinery provides the highest level of technical support

Protect your investment

If your machine will be working in severe conditions, or you want to minimise repair costs, you can take advantage of a unique extended warranty programme called HELP (Hitachi Extended Life Program) and comprehensive service contracts. These can help to optimise performance, reduce downtime and ensure a higher resale value.

We apply the same technological expertise to our wide range of high-quality parts as we do our machines. As a result, you can minimise unscheduled downtime and ensure maximum availability.

The parts range includes Hitachi Construction Machinery Genuine Parts, Performance Parts, filters, undercarriages, and remanufactured components. We also offer ground engaging tools and buckets, which have been manufactured to the same exacting standards.

As your business grows, you may need to extend your fleet to meet the demands of new contracts. Why not try before you buy with the Hitachi Construction Machinery Premium Rental programme? This gives you immediate access to Zaxis-7 excavators for a period of one month to a year.

Along with the reliability, quality and service you would expect from the Hitachi Construction Machinery brand, Premium Rental offers flexible contracts and fixed costs that make it easier for you to budget.

18 | ZX95US excavators | 19



GET more from your machine

Designed to work in perfect harmony with your machine, our durable hydraulic breakers, buckets and ground engaging tools (GET) will increase your profit by maximising productivity and uptime. Manufactured to the same high standards as all Hitachi Construction Machinery equipment, they offer unrivalled reliability and exceptional performance.

Buckets


You can increase the versatility of your excavator by choosing the right bucket for the job. For loading light materials or heavy-duty work, our buckets can be customised to meet your needs. You have a wide range of options to choose from - including GD, HD and XHD buckets with different capacities and widths - and guick coupler connections such as CW, pin grabber and S-coupling are also available.

Ground engaging tools

You can enhance the digging power and productivity of your excavator with Hitachi Construction Machinery GET. Quick and safe to install and replace, they fit precisely to your attachments and can be tailored to suit the task. Using GET can reduce your maintenance costs and downtime, lower fuel consumption and enhance the overall performance of your machine.

Breakers

High-performance hydraulic breakers – approved by Hitachi Construction Machinery – are perfectly suited to compact excavators. They are easy to maintain and user-friendly, and their high-quality materials ensure a long lifetime. This means reduced maintenance costs, fewer replacement parts and minimal downtime.



Hitachi buckets, GET and breakers are manufactured to the same high standards as all Hitachi construction equipment.



Hitachi Construction Machinery offers a wide variety of attachments to suit your application.



Hitachi breakers are lightweight with high impact energy.



Hitachi GET include self-sharpening teeth and reliable adapters to ensure a precise fit.

ZX95US excavators | 21

Range overview

The perfect tool for the job

You can find the perfect machine to meet your needs within the range of ZX95US excavators, designed to make your life easier in tough environments. The standard mono boom provides excellent lifting power, while the two-piece boom configuration offers greater versatility for lower working heights or high-reach applications. For tasks that require an extended working range, such as slope finishing and dredging, the super long front model (SLF) is the ideal choice.



ZX95USB-7 MONO BOOM

VERSATILITY AND WIDE REACH

Operating weight $8\,760-9\,810~kg$ Bucket ISO heaped $0.28~m^3$ Nominal power 50.4~kW



ZX95USB-7 2-PIECE BOOM VERSATILITY AND DEEP REACH

Operating weight 9 150 – 10 200 kg Bucket ISO heaped 0.28 m³ Nominal power 50.4 kW







In control of your world

When you take delivery of your new machine, you become part of the latest generation of a global family. With a 70-year heritage in designing hydraulic excavators, and a reputation as the industry's leading mining machine manufacturer, the Hitachi Construction Machinery network will give you access to a range of exceptional equipment.

Hitachi Construction Machinery excavators, wheel loaders, rigid dump trucks and special application machines incorporate advanced technology and pioneering expertise. Made at state-of-the-art facilities, they are built to the highest standards. You'll also benefit from market-leading services and initiatives, such as Premium Rental and Premium Used, which have been created to enhance your experience as a customer.

Whatever vision you wish to create, Hitachi Construction Machinery has the product, people, solutions and services you need to make it become a reality – and empower you to take control of your world.



Mini excavators









Special application excavators



ZW wheel loaders

24 | Hitachi Construction Machinery

SPECIFICATIONS

ENGINE	
Model	4TNV98CT
Туре	4-cycle water-cooled, common rail direct injection exhaust turbo charger
Aspiration	Cooled EGR
Aftertreatment	Muffler filter
No. of cylinders	4
Rated power	
ISO 14396 : 2002 gross	50.4 kW at 2 000 min ⁻¹
ISO 9249 : 2007 net	49.8 kW at 2 000 min ⁻¹
Maximum torque	292.9 Nm at 1 300 min ⁻¹
Piston displacement	3.318 L
Bore and stroke	98 mm x 110 mm
Batteries	2 x 12 V / 60 Ah

HYDRAULIC	SYSTEN	Л			
Hydraulic Pumps					
Main pumps		3 variable di	splacement axial	piston pumps	
Maximum oil fl		2 x 72 L/mir	า		
iviaximum oii ii	OW	1 x 56 L/mir	า		
Pilot pump		1 gear pump	0		
Maximum oil fl	OW	20.0 L/min			
Hydraulic Mo	otors				
Travel		2 variable di	2 variable displacement axial piston motors		
Swing		1 axial pisto	1 axial piston motor		
Relief Valve	Setting	S			
Implement circ	uit	28.0 MPa			
Swing circuit		26.5 MPa			
Travel circuit		31.4 MPa			
Pilot circuit		3.9 MPa	3.9 MPa		
Hydraulic Cylinders					
	Quantity	Bore	Rod diameter	Stroke	
Boom	1	115 mm	70 mm	802 mm	
Arm	1	95 mm	60 mm	900 mm	

UPPER STRUCTURE					
Revolving Frame					
D-section frame for re	esistance to deformation				
Swing Device					
Axial piston motor with planetary reduction gear is bathed in oil. Swing circle is single-row. Swing parking brake is spring-set/hydraulic-released disc type.					
Swing speed	10.1 min ⁻¹				
Swing torque	16.6 kNm				
Operator's Cab					
Independent spacious cab, 1 025 mm wide by 1 654 mm high, conforming to ISO* Standards. Reinforced glass windows on 4 sides for visibility. Front windows (upper and lower) can be opened. Reclining seat. * International Organization for Standarization					

85 mm

120 mm

55 mm

70 mm

730 mm

145 mm

Bucket

Blade

UPPER STRUCTURE					
Revolving Frame	Revolving Frame				
D-section frame for resi	istance to deformation				
Swing Device					
Axial piston motor with planetary reduction gear is bathed in oil. Swing circle is single-row. Swing parking brake is spring-set/hydraulic-released disc type.					
Swing speed	10.1 min ⁻¹				
Swing torque	16.6 kNm				
Operator's Cab					
Independent spacious cab, 1 025 mm wide by 1 654 mm high, conforming to ISO* Standards. Reinforced glass windows on 4 sides for visibility. Front windows (upper and lower) can be opened. Reclining seat. * International Organization for Standarization					

UNDERCARRIAGE				
Tracks				
materials.	Tractor-type undercarriage. Welded track frame using selected materials. Side frame welded to track frame			
Numbers of Rollers	s on Each Side			
Upper rollers	1			
Lower rollers	5			
Track shoes	Track shoes 40			
Travel Device				
Each track driven by 2-speed axial piston motor. Parking brake is spring-set/hydraulic-released disc type. Automatic transmission system: High-Low.				
Traval appeda	High: 0 to 5.0 km/h			
Traver speeds	Travel speeds Low: 0 to 3.1 km/h			
Maximum traction force	n force 65.2 kN			
Gradeability	70% (35 degree) continuous			

SERVICE REFILL CAPACITIES				
Fuel tank	125.0 L			
Engine coolant	13.1 L			
Engine oil	12.3 L			
Travel device (each side)	1.2 L			
Hydraulic system	110.0 L			
Hydraulic oil tank	52.0 L			

ENVIRONMENT				
Engine Emissions	EU Stage V			
Sound Level				
Sound level in cab according to ISO LpA 70 dB(A)				
External sound level according to ISO6395: 2008 and EU Directive LwA 99 dB(A) 2000/14/EC				
Air Conditioning System				
The air conditioning system contains fluorinated greenhouse gases. Refrigerant type: HFO-1234yf, GWP: 4, Amount: 0.65 kg, CO ₂ e: 0.0026 ton				

WEIGHTS AND GROUND PRESSURE

Operating Weight and Ground Pressure

		ZX95US-7		
Boom type		Monoblock		
Blade type	Shoe type	Shoe width (mm)	kg	kPa
	Grouser shoe	450	8 410	37
STD	Grouser snoe	600	8 590	29
310	Rubber shoe	450	8 320	37
	Pad crawler shoe	450	8 450	37
	Grouser shoe GLE (OPT) Rubber shoe	450	8 760	42
ANCLE (ODT)		600	8 940	42
ANGLE (OPT)		450	8 670	41
	Pad crawler shoe	450	8 800	42

Including 0.28 m³ (ISO 7451:2007 heaped) bucket weight 211 kg and counterweight 1 165 kg + additional counterweight 430 kg.

		ZX95	SUS-7	
Boom type		2-Piece boom		
Blade type	Shoe type	Shoe width (mm)	kg	kPa
	Grouser shoe	450	9 400	44
STD	Rubber shoe	450	9 310	44
	Pad crawler shoe	450	9 440	45

Including 0.28 m³ (ISO 7451:2007 heaped) bucket weight 211 kg and counterweight 1 165 kg + additional counterweight 430 kg.

Operating Weight and Ground Pressure

			ZX95USB-7			
	Boom type		Monoblock		2-Piece	
Blade type	Shoe type	Shoe width (mm)	kg	kPa	kg	kPa
	Grouser shoe	450	8 850	39	9 240	41
STD	Grouser snoe	600	9 030	30	9 240	31
310	Rubber shoe	450	8 760	39	9 150	41
	Pad crawler shoe	450	8 890	39	9 280	41
	0	450	9 200	43	9 590	45
ANOLE (ODT)	Grouser shoe	600	9 380	45	9 770	46
ANGLE (OPT)	Rubber shoe	450	9 110	43	9 500	45
	Pad crawler shoe	450	9 240	44	9 630	46

Including 0.28 m³ (ISO 7451:2007 heaped) bucket weight 211 kg and counterweight 1 165 kg + additional counterweight 430 kg.

Operating Weight and Ground Pressure

		ZX95US-7 SLF		
Blade type	Shoe type	Shoe width (mm)	kg	kPa
	Grouser shoe	450	9 130	43
STD	Rubber shoe	450	9 040	43
	Pad crawler shoe	450	9 170	44

 $Including \ 0.13 \ m^3 \ (ISO \ ISO \ 7451:2007 \ heaped) \ bucket \ weight \ 141 \ kg \ and \ counterweight \ 1 \ 165 \ kg \ and \ additional \ counterweight \ 430 \ kg.$

26 | 27

BUCKET AND ARM DIGGING FORCE

Unit: kN

	ZX95US-7		
Boom type	Monoblock boom	2-Piece boom	
Arm length	2.12 m	1.62 m	
Bucket digging force* ISO 6015 : 2006	57.5	57.5	
Bucket digging force SAE : PCSA	50.1	50.1	
Arm crowd force* ISO 6015 : 2006	34.5	40.2	
Arm crowd force SAE : PCSA	33.0	38.1	

^{*} Calculated value at power boost

BUCKET AND ARM DIGGING FORCE

Unit: kN

	ZX95USB-7		
Boom type	Monoblock boom	2-Piece boom	
Arm length	2.12 m	1.62 m	2.12 m
Bucket digging force* ISO 6015 : 2006	57.5	57	7.5
Bucket digging force SAE : PCSA	50.1	50.1	
Arm crowd force* ISO 6015 : 2006	34.5	40.2	34.5
Arm crowd force SAE : PCSA	33.0	38.1	33.0

^{*} Calculated value at power boost

BUCKET AND ARM DIGGING FORCE

Unit: kN

	ZX95US-7 SLF
Arm length	4.04 m
Bucket digging force* ISO 6015 : 2006	57.5
Bucket digging force SAE : PCSA	50.1
Arm crowd force* ISO 6015 : 2006	20.3
Arm crowd force SAE : PCSA	19.8

^{*} Calculated value at power boost

MEMO _____

SPECIFICATIONS

ZX95US-7

WORKING RANGES metre 9 8 E,I 6 5 4 3 D 2 D' 0 Α В 2 ____2.12 m 3 4 5 6 1 0 metre 9 8 7 6 5 4 3 2 The illustrations are with additional counterweight.


Unit: mm

	Offic. Hilli
	ZX95US-7
	Monoblock boom
Arm length	2.12 m
A Max. digging reach	6 870
A' Max. digging reach (on ground)	6 720
B Max. digging depth	4 650
C Max. cutting height	7 580
D Max. dumping height	5 480
D' Min. dumping height	1 950
E Min. swing radius	2 120
F Max. vertical wall digging depth	4 260
G Front height at Min. swing radius	5 570
H Min. level crowding distance	1 630
I Working radius at Min. swing radius (Max. boom-swing angle)	-

Excluding track shoe lug

SPECIFICATIONS

ZX95US-7



Unit: mm

		Unit: mm
		ZX95US-7
		Monoblock boom
Α	Distance between tumblers	2 295
В	Undercarriage length	2 900
*C	Counterweight clearance	720
D	Rear-end swing radius	1 390 (1 490 with additional counterweight)
D'	Rear-end length	1 390 (1 490 with additional counterweight)
Е	Overall width of upperstructure	2 260
F	Overall height of cab	2 530
*G	Min. ground clearance	360
Н	Track gauge	1 750
I	Track shoe width	G 450
J	Undercarriage width	2 200
K	Overall width	2 260
L	Track height	610
М	Overall length	
IVI	With Arm 2.12 m	6 330
N	Overall height of boom	
IN	With Arm 2.12 m	2 930
0	Engine cover-height	1 880
Р	Distance between the front end of blade and the axis of rotation	1 890
Q	Blade height	472
R	Blade bottom highest position above ground	370
S	Blade bottom lowest position above ground	290

Excluding track shoe lug G : Grouser shoe

SPECIFICATIONS

ZX95US-7 2-PIECE BOOM

WORKING RANGES metre 9 8 7 6 5 С 3 2 D' 0 Α В 2 ——1.62 m 3 5 9 8 7 6 5 4 3 2 1 0 _{metre}


U	nı	τ:	r	nı	r

	ZX95US-7
	2-Piece boom
Arm length	1.62 m
A Max. digging reach	7 540
A' Max. digging reach (on ground)	7 410
B Max. digging depth	4 250
C Max. cutting height	8 780
D Max. dumping height	6 830
D' Min. dumping height	1 870
E Min. swing radius	2 020
F Max. vertical wall digging depth	3 890
G Front height at Min. swing radius	6 660
H Min.level crowding distance	1 630
I Working radius at Min. swing radius (Max. boom-swing angle)	-

Excluding track shoe lug

SPECIFICATIONS

ZX95US-7 2-PIECE BOOM




Unit: mm

		-
		ZX95US-7
		2-Piece boom
Α	Distance between tumblers	2 295
В	Undercarriage length	2 900
* C	Counterweight clearance	720
D	Rear-end swing radius	1 490
D'	Rear-end length	1 490
Е	Overall width of upperstructure	2 260
F	Overall height of cab	2 530
* G	Min. ground clearance	360
Н	Track gauge	1 750
- 1	Track shoe width	G 450
J	Undercarriage width	2 200
K	Overall width	2 260
L	Track height	610
М	Overall length	
IVI	With Arm 1.62 m	6 360
N	Overall height of boom	
IN	With Arm 1.62 m	2 680
0	Engine cover-height	1 880
Р	Distance between the front end of blade and the axis of rotation	1 890
Q	Blade height	472
R	Blade bottom highest position above ground	370
S	Blade bottom lowest position above ground	290

 $\dot{}$ Excluding track shoe lug $\,$ G : Grouser shoe

WORKING RANGES



The illustrations are with additional counterweight.

Unit: mm


	ZX95USB-7		
	Monoblock boom	2-Piece	e boom
Arm length	2.12 m	1.62 m	2.12 m
A Max. digging reach	7 560	7 610	8 060
A' Max. digging reach (on ground)	7 420	7 470	7 920
B Max. digging depth	4 530	3 760	4 260
C Max. cutting height	7 190	7 690	8 040
D Max. dumping height	5 120	5 590	5 930
D' Min. dumping height	1 660	2 730	2 300
E Min. swing radius	2 680	2 750	3 020
F Max. vertical wall digging depth	3 900	3 650	4 110
G Front height at Min. swing radius	5 350	5 810	5 830
H Min. level crowding distance	2 130	980	720
I Working radius at Min. swing radius (Max. boom-swing angle)	2 210	2 080	2 210
Offset distance (May been quing angle)	860	860	860
J' Offset distance (Max. boom-swing angle)	730	730	730
Max. boom-swing angle (deg.)	65 /55	65 /55	65 /55

Excluding track shoe lug

SPECIFICATIONS

ZX95USB-7

DIMENSIONS



The illustrations are with additional counterweight.

I leite enen

35

			Unit: mm	
		ZX95USB-7		
		Monoblock boom	2-Piece boom	
Α	Distance between tumblers	2 295	2 295	
В	Undercarriage length	2 900	2 900	
*C	Counterweight clearance	720	720	
D	Rear-end swing radius	1 590 (1 690 with additional counterweight)	1 590 (1 690 with additional counterweight)	
D'	Rear-end length	1 590 (1 690 with additional counterweight)	1 590 (1 690 with additional counterweight)	
Е	Overall width of upperstructure	2 260	2 260	
F	Overall height of cab	2 530	2 530	
*G	Min. ground clearance	360	360	
Н	Track gauge	1 750	1 750	
I	Track shoe width	450	450	
J	Undercarriage width	2 200	2 200	
K	Overall width	2 260	2 260	
L	Track height	610	610	
	Overall length			
М	With Arm 1.62 m	-	7 610	
	With Arm 2.12 m	7 220	7 600	
	Overall height of boom			
Ν	With Arm 1.62 m	-	2 530	
	With Arm 2.12 m	2 530	2 780	
0	Engine cover-height	1 880	1 880	
Р	Distance between the front end of blade and the axis of rotation	2 010	2 010	
Q	Blade height	472	472	
R	Blade bottom highest position above ground	390	390	
S	Blade bottom lowest position above ground	340	340	

^{*} Excluding track shoe lug G : Grouser shoe

SPECIFICATIONS

ZX95US-7 SUPER LONG FRONT

WORKING RANGES meter 12 11 10 9 8 6 5 D 3 2 0 -2 ——4.04 m 3 В 5 6 8 14 13 12 11 10 9 8 7 6 5 4 3 2 1 0 meter


U	nıt	: r	nr

	ZX95US-7 SLF
	SLF boom
Arm length	4.04 m
A Max. digging reach	10 220
A' Max. digging reach (on ground)	10 120
B Max. digging depth	7 010
C Max. cutting height	11 070
D Max. dumping height	8 980
D' Min. dumping height	1 950
E Min. swing radius	1 750
F Front height at Min. swing radius	7 470
G Min.level crowding distance	1 630

Excluding track shoe lug

SPECIFICATIONS

ZX95US-7 SUPER LONG FRONT



Unit: mm

		ZX95US-7 SLF
		SLF boom
А	Distance between tumblers	2 295
В	Undercarriage length	2 900
* C	Counterweight clearance	720
D	Rear-end swing radius	1 490
D'	Rear-end length	1 490
Е	Overall width of upperstructure	2 260
* F	Overall height of cab	2 530
G	Min. gound clearance	360
Н	Track gauge	1 750
I	Track shoe width	G 450
J	Undercarriage width	2 200
K	Overall width	2 260
L	Track height	610
М	Overall length	
IVI	With 4.04 m arm	8 100
N	Overall height of boom	
IN	With 4.04 m arm	2 700
0	Engine cover-height	1 880
Р	Distance between the front end of blade and the axis of rotation	1 890
Q	Blade height	472
R	Blade bottom highest position above ground	370
S	Blade Bottom lowest position above ground	290

*Excluding track shoe lug G: Grouser shoe

MACHINE CAPACITIES

ZX95US-7

Notes: 1. Ratings are based on ISO 10567: 2007.

- 2. Machine capacity does not exceed 75% of tipping load with the machine on firm, level ground or 87% full hydraulic capacity.
- 3. The load point is the center-line of the bucket pivot mounting pin on the arm.
- 4. *Indicates load limited by hydraulic capacity.
- 5. 0 m = Ground.

For machine capacities, subtract installed attachment and quick coupler weight from machine capacities.

To determine lifting capacities, apply "Rating over-side or 360 degrees" machine capacities from the table and deduct weight of installed attachment and quick coupler.

Optional feature may affect machine performance.

A: Load radius B: Load point height C: Machine capacity



ZA

	Load						Load	radius						-side or 360		
Conditions	point	1.0) m	2.0) m	3.0) m	4.0) m	5.0) m	6.0	0 m	1 A	t max. read	:h
	height (m)	Ů	₽	ů	₽	ů	₽	Ů	₽	ů	₽	ů	₽	ů	₽	meter
oom 3.72 m m 2.12 m ounterweight	5.0							*1 480	*1 480					*1 420	*1 420	4.52
165 kg ouser shoe 60 mm	4.0					*1 450	*1 450	*1 520	*1 520	*1 600	1 360			*1 330	1 280	5.18
	3.0			*2 380	*2 380	*1 940	*1 940	*1 750	*1 750	1 650	1 340			*1 310	1 110	5.58
	2.0					*2 650	*2 650	*2 090	1 830	1 610	1 300			1 270	1 030	5.78
	1.0					*3 310	2 640	2 190	1 740	1 560	1 260			1 250	1 000	5.79
	0 (Ground)					3 320	2 530	2 120	1 670	1 520	1 220			1 280	1 030	5.63
	-1.0	*2 410	*2 410	*3 890	*3 890	3 270	2 490	2 080	1 640	1 510	1 200			1 400	1 120	5.27
	-2.0	*3 960	*3 960	*5 210	4 980	3 280	2 490	2 080	1 640					1 670	1 330	4.67
	-3.0			*4 260	*4 260	*2 950	2 550							*2 210	1 880	3.71
oom 3.72 m m 2.12 m ounterweight	5.0							*1 480	*1 480					*1 420	*1 420	4.52
595 kg ouser shoe 60 mm	4.0					*1 450	*1 450	*1 520	*1 520	*1 600	1 550			*1 330	*1 330	5.18
	3.0			*2 380	*2 380	*1 940	*1 940	*1 750	*1 750	*1 670	1 530			*1 310	1 270	5.58
	2.0					*2 650	*2 650	*2 090	2 070	1 820	1 490			*1 340	1 180	5.78
	1.0					*3 310	3 000	*2 430	1 980	1 770	1 440			1 420	1 160	5.79
	0 (Ground)					*3 680	2 890	2 400	1 910	1 740	1 400			1 460	1 190	5.63
	-1.0	*2 410	*2 410	*3 890	*3 890	3 710	2 850	2 370	1 880	1 720	1 390			1 590	1 290	5.27
	-2.0	*3 960	*3 960	*5 210	*5 210	*3 570	2 850	2 370	1 880					1 900	1 530	4.67
	-3.0			*4 260	*4 260	*2 950	2 910							*2 210	2 140	3.71

MACHINE CAPACITIES

ZX95US-7 2-PIECE BOOM

Notes: 1. Ratings are based on ISO 10567 : 2007.

- 2. Machine capacity does not exceed 75% of tipping load with the machine on firm, level ground or 87% full hydraulic capacity.
- 3. The load point is the center-line of the bucket pivot mounting pin on the arm.
- 4. *Indicates load limited by hydraulic capacity.
- 5. 0 m = Ground.

For machine capacities, subtract installed attachment and quick coupler weight from machine capacities.

To determine lifting capacities, apply "Rating over-side or 360 degrees" machine capacities from the table and deduct weight

of installed attachment and quick coupler.

Optional feature may affect machine performance.

ZAXIS 95US-7 2-Piece boom. Blade above Ground

B: Load point height C: Machine capacity

ZAXIS 95US	S-7 2-Pied	e boom	n, Blade	above	Ground					🖁 Ratir	ng over-fror	nt 🗯 F	Rating over-	side or 360) degrees	Unit : kg
	Load						Load	radius						Δ.		la .
Conditions	point	1.0) m	2.0) m	3.0) m	4.0	m	5.0	m	6.0) m	A	t max. reac	n
Conditionic	height (m)	ů	₽	ů	₽	ů	₽	ů	₽	ů	₽	ů	₽	ů	₽	meter
2 piece boom Arm 1.62 m Counterweight	6.0					*2 930	*2 930	*2 410	2 100					*1 980	1 650	4.52
1 595 kg Grouser shoe 450 mm	5.0			*2 230	*2 230	*2 820	*2 820	*2 410	2 090	1 790	1 440			1 550	1 240	5.37
400 11111	4.0							*2 490	2 010	1 760	1 410			1 300	1 040	5.93
	3.0							2 390	1 880	1 700	1 360	1 280	1 020	1 170	940	6.28
	2.0									1 640	1 300	1 250	1 000	1 120	890	6.46
	1.0									1 590	1 250	1 230	970	1 110	880	6.47
	0 (Ground)							*2 070	1 660	1 560	1 230	1 220	970	*970	910	6.33

MACHINE CAPACITIES

ZX95USB-7

Notes: 1. Ratings are based on ISO 10567: 2007.

- 2. Machine capacity does not exceed 75% of tipping load with the machine on firm, level ground or 87% full hydraulic capacity.
- 3. The load point is the center-line of the bucket pivot mounting pin on the arm.
- 4. *Indicates load limited by hydraulic capacity.
- 5.0 m = Ground.

For machine capacities, subtract installed attachment and quick coupler weight from machine capacities.

To determine lifting capacities, apply "Rating over-side or 360 degrees" machine capacities from the table and deduct weight of installed attachment and quick coupler.

Optional feature may affect machine performance.

A: Load radius B: Load point height C: Machine capacity

	Load						Load	radius						_	t max. read	nh.
Conditions	point	1.	0 m	2.0) m	3.0) m	4.0) m	5.0) m	6.0) m	^	ii iiiax. iead	
	height (m)	ů	₽	ů	₽	ů	₽	ů	₽	ů	₽	Ů	₽	ů	₽	meter
om 3.55 m n 2.12 m unterweight	5.0									1 780	1 460			1 720	1 400	5.10
65 kg ouser shoe) mm	4.0							*1 960	*1 960	1 780	1 460			1 380	1 130	5.82
	3.0							*2 380	2 010	1 740	1 420	1 300	1 060	1 210	990	6.25
	2.0					3 720	2 880	2 360	1 890	1 680	1 370	1 270	1 030	1 130	920	6.46
	1.0					*2 740	2 640	2 240	1 780	1 620	1 310	1 240	1 000	1 100	890	6.49
	0 (Ground)					*3 130	2 560	2 160	1 710	1 570	1 260	1 210	980	1 130	910	6.33
	-1.0			*2 650	*2 650	3 350	2 550	2 130	1 680	1 550	1 240			1 220	980	5.96
	-2.0			*4 310	*4 310	3 380	2 570	2 140	1 690	1 560	1 250			1 430	1 150	5.34
	-3.0					*3 390	2 640	2 190	1 730					1 970	1 570	4.31
oom 3.55 m m 2.12 m ounterweight	5.0									*1 940	1 660			*1 750	1 600	5.10
95 kg buser shoe	4.0							*1 960	*1 960	*1 940	1 660			1 560	1 290	5.82
, 111111	3.0							*2 380	2 270	1 970	1 620	1 480	1 220	1 380	1 140	6.25
	2.0					4 190	3 270	2 670	2 160	1 910	1 560	1 450	1 190	1 290	1 060	6.46
	1.0					*2 740	*2 740	2 550	2 040	1 850	1 500	1 420	1 160	1 260	1 040	6.49
	0 (Ground)					*3 130	2 950	2 470	1 970	1 800	1 460	1 400	1 140	1 300	1 060	6.33
	-1.0			*2 650	*2 650	3 830	2 940	2 440	1 940	1 780	1 440			1 400	1 140	5.96
	-2.0			*4 310	*4 310	3 850	2 960	2 450	1 950	1 780	1 440			1 630	1 330	5.34
	-3.0					*3 390	3 030	*2 380	2 000					*2 050	1 800	4.31

MACHINE CAPACITIES

ZX95USB-7


Notes: 1. Ratings are based on ISO 10567: 2007.

- 2. Machine capacity does not exceed 75% of tipping load with the machine on firm, level ground or 87% full hydraulic capacity.
- 3. The load point is the center-line of the bucket pivot mounting pin on the arm.
- 4. *Indicates load limited by hydraulic capacity.
- 5. 0 m = Ground.

For machine capacities, subtract installed attachment and quick coupler weight from machine capacities.

To determine lifting capacities, apply "Rating over-side or 360 degrees" machine capacities from the table and deduct weight of installed attachment and quick coupler.

Optional feature may affect machine performance.



A: Load radius B: Load point height C: Machine capacity

ZX

	Load						Load	radius				nt □ ■ R				
Conditions	point	1.	0 m	2.0) m	3.0) m	4.0) m	5.0) m	6.0) m	A	t max. read	:n
	height (m)	ů	₽	ů	₽	ů	₽	ů	₽	ů	₽	ď	₽	ď	₽	meter
300m 3.93 m Arm 1.62 m Counterweight	5.0							*2 470	2 070	1 730	1 390			1 620	1 300	5.16
165 kg Grouser shoe 150 mm	4.0							2 510	2 010	1 730	1 390			1 280	1 020	5.87
	3.0					*2 960	*2 960	2 360	1 870	1 660	1 330	1 220	980	1 120	890	6.30
	2.0							2 170	1 690	1 570	1 240	1 190	940	1 030	810	6.51
	1.0							2 020	1 550	1 490	1 160	1 140	900	1 000	790	6.54
	0 (Ground)							1 960	1 500	1 440	1 120	1 120	870	1 020	800	6.38
	-1.0					*2 980	2 290	1 950	1 490	1 420	1 100	1 110	870	1 110	870	6.01
	-2.0					*2 940	2 340	1 980	1 510	1 440	1 120			1 310	1 020	5.40
	-3.0															
Room 3.93 m rm 2.12 m Counterweight	5.0							*2 140	2 120	1 780	1 430			1 350	1 080	5.75
165 kg Grouser shoe 50 mm	4.0							*2 310	2 060	1 750	1 410	1 260	1 010	1 110	880	6.38
00 11111	3.0							2 420	1 920	1 680	1 340	1 230	980	980	770	6.77
	2.0							2 210	1 730	1 580	1 240	1 180	930	910	710	6.96
	1.0							2 030	1 560	1 480	1 150	1 130	880	880	680	6.99
_	0 (Ground)							1 920	1 460	1 410	1 080	1 080	840	890	690	6.84
	-1.0					*2 920	2 180	1 890	1 420	1 370	1 050	1 060	820	950	730	6.51
	-2.0					3 020	2 220	1 900	1 430	1 370	1 050			1 090	840	5.95
	-3.0															

MACHINE CAPACITIES

ZX95USB-7

Notes: 1. Ratings are based on ISO 10567: 2007.

- 2. Machine capacity does not exceed 75% of tipping load with the machine on firm, level ground or 87% full hydraulic capacity.
- 3. The load point is the center-line of the bucket pivot mounting pin on the arm.
- 4. *Indicates load limited by hydraulic capacity.
- 5. 0 m = Ground.

For machine capacities, subtract installed attachment and quick coupler weight from machine capacities.

To determine lifting capacities, apply "Rating over-side or 360 degrees" machine capacities from the table and deduct weight of installed attachment and quick coupler.

Optional feature may affect machine performance.

A: Load radius

B: Load point height C: Machine capacity

ZX95USB-7	2-Piece	e boom	, Blade	above (Ground					🗓 Ratii	ng over-fror	nt 🗯 F	Rating over-	side or 36	0 degrees	Unit : kg
	Load							radius						A	At max, read	ch
Conditions	point height) m		0 m) m) m) m) m			···
	(m)	ů	₽	ů	₽	ů	₽	ů	₽	ů	₽	ů	₽	ů	₽	meter
Boom 3.93 m Arm 1.62 m Counterweight	5.0							*2 470	2 330	1 960	1 590			1 840	1 490	5.16
1 595 kg Grouser shoe 450 mm	4.0							*2 640	2 270	1 950	1 590			1 470	1 190	5.87
	3.0					*2 960	*2 960	2 670	2 130	1 890	1 520	1 410	1 130	1 290	1 040	6.30
	2.0							2 480	1 950	1 800	1 440	1 370	1 100	1 190	960	6.51
	1.0							2 330	1 820	1 720	1 360	1 330	1 060	1 160	930	6.54
	0 (Ground)							2 270	1 760	1 660	1 310	1 300	1 030	1 190	950	6.38
	-1.0					*2 980	2 680	2 260	1 750	1 650	1 300	1 290	1 030	1 290	1 020	6.01
	-2.0					*2 940	2 730	2 280	1 770	1 670	1 310			1 470	1 200	5.40
	-3.0															
Boom 3.93 m Arm 2.12 m Counterweight	5.0							*2 140	*2 140	*1 990	1 630			1 540	1 250	5.75
1 595 kg Grouser shoe 450 mm	4.0							*2 310	*2 310	1 980	1 610	1 440	1 160	1 280	1 030	6.38
450 11111	3.0							*2 720	2 180	1 900	1 540	1 410	1 140	1 130	910	6.77
	2.0							2 520	1 990	1 800	1 440	1 360	1 090	1 060	840	6.96
	1.0							2 340	1 820	1 710	1 350	1 310	1 040	1 030	810	6.99
	0 (Ground)							2 230	1 720	1 630	1 280	1 260	1 000	1 050	820	6.84
	-1.0					*2 920	2 570	2 190	1 690	1 600	1 250	1 240	980	1 110	880	6.51
	-2.0					3 500	2 610	2 200	1 690	1 600	1 250			1 270	1 000	5.95
	-3.0															

MACHINE CAPACITIES

ZX95US-7 SUPER LONG FRONT


- Notes: 1. Ratings are based on ISO 10567: 2007.
 - 2. Machine capacity does not exceed 75% of tipping load with the machine on firm, level ground or 87% full hydraulic capacity.
 - 3. The load point is the center-line of the bucket pivot mounting pin on the arm.
 - 4. *Indicates load limited by hydraulic capacity.
 - 5. 0 m = Ground.

For machine capacities, subtract installed attachment and quick coupler weight from machine capacities.

To determine lifting capacities, apply "Rating over-side or 360 degrees" machine capacities from the table and deduct weight

of installed attachment and quick coupler.

Optional feature may affect machine performance.



A: Load radius

		B: Load point heigh
	В	C: Machine capaci
;	'	

ZX95US-7 I	Monobloo	k boo	m, B	lade a	above	Grou	ınd						Ů	Rating o	ver-front	₽	Rating	over-sic	de or 36	0 degre	es U	nit : kg
	Load							1 40		Load				7.0		0.0		0.0		At	max. rea	ach
Conditions	point height) m) m	3.0) m) m) m	7.0) m) m			
	(m)	ů	₽	ů	₽	ů	₽	ů	₽	Ů	₽	ů	₽	ů	₽	ů	₽	ů	₽	ů	₽	meter
Boom 5.48 m Arm 4.04 m	8.0									*990	*990	*770	*770							*600	*600	6.31
Counterweight 1 595 kg Grouser shoe	7.0									*950	*950	*940	*940	*700	*700					*550	*550	7.23
450 mm	6.0									*960	*960	*940	*940	*920	*920					*530	*530	7.91
	5.0							*1 080	*1 080	*1 030	*1 030	*980	*980	*930	*930	*810	710			*520	*520	8.42
	4.0							*1 270	*1 270	*1 150	*1 150	*1 050	*1 050	*980	910	870	700			*520	*520	8.79
	3.0			1 880	1 880	*1 900	*1 900	*1 530	*1 530	*1 300	*1 300	*1 140	1 140	*1 030	870	840	680	*560	520	*530	520	9.03
	2.0					*2 480	*2 480	*1 820	*1 820	*1 470	1 420	*1 250	1 070	1 030	820	810	650	650	510	*550	490	9.15
	1.0					*2 950	*2 690	*2 090	1 800	*1 630	1 310	1 250	1 000	980	780	780	620	630	490	*580	480	9.16
	0 (Ground)			990	990	*2 300	*2 300	2 140	1 650	1 550	1 220	1 180	930	940	740	760	590	620	480	*630	470	9.06
	-1.0	940	940	1 300	1 300	*2 280	*2 280	2 040	1 560	1 470	1 150	1 130	890	900	700	740	570			*690	480	8.84
	-2.0	1 320	1 320	1 690	1 690	*2 580	2 310	1 990	1 510	1 430	1 110	1 100	860	880	680	720	560			660	510	8.50
	-3.0	1 720	1 720	2 140	2 140	*2 830	2 320	1 970	1 500	1 420	1 090	1 090	840	870	680	730	560			720	560	8.02
	-4.0			2 670	2 670	*24 90	2 360	*1 940	1 520	1 420	1 100	1 100	850	890	690					830	640	7.37
	-5.0			2 630	2 630	*2 010	*2 010	*1 600	1 570	*1 280	1 130	*990	880							*830	800	6.51

ENGINE	ZX95US-7	ZX95US-7 2-piece	ZX95USB-7
Aftertreatment device	•	•	•
Air cleaner double filters	•	•	•
Alternator 24 V - 60 A	•	•	•
Auto idle system	•	•	•
Auto shut-down control	•	•	•
Cartridge-type engine oil filter	•	•	•
Cartridge-type fuel main filter	•	•	•
ConSite OIL (sensor)	0	0	0
Dry-type air filter with evacuator valve (with air filter restriction indicator)	•	•	•
Electric fuel refilling pump	•	•	•
Engine oil drain coupler	•	•	•
Fan guard	•	•	•
Fuel cooler	•	•	•
Fuel pre-filter with water separator	•	•	•
Pre-cleaner	0	0	0
PWR / ECO mode control	•	•	•
Radiator reserve tank	•	•	•
Radiator, oil cooler with one touch type cleaning interval extension net	0	0	0
Radiator, oil cooler with one touch type dust-proof indoor net	•	•	•

HYDRAULIC SYSTEM	ZX95US-7	ZX95US-7 2-piece	ZX95USB-7
Auxiliary flow adjustment switching	0	•	0
Boom anti-drift valve	•	•	•
ConSite OIL (sensor)	0	0	0
Extra port for control valve	•	•	•
Full-flow filter	•	•	•
Hose rupture valve for arm cylinder	•	•	•
Hose rupture valve for boom cylinder	•	•	•
Hydraulic pilot type control levers	•	•	•
Low-temperature starting speed control	•	•	•
Main pump pressure and temperature sensor	•	•	•
Pilot control shut-off lever with neutral engine start system	•	•	•
Pilot filter	•	•	•
Suction filter	•	•	•
Swing drain filter	•	•	•
Swing parking brake	•	•	•
Travel parking brake	•	•	•
Two-speed travel system	•	•	•
Valve for extra piping	•	•	•
Variable reliefvalve for breaker and crusher	•	•	•
Work mode selector	•	•	•

CAB	ZX95US-7	ZX95US-7	ZX95USB-7
AUX function lever (breaker)	0	2-piece	0
,		_	
Blade lever with two-speed travel switch Bluetooth® integrated DAB+radio	•	•	
Cab with laminate glass only for front		•	•
window	0	0	0
Control lever auto-lock	•	•	•
Defroster	•	•	•
Drink holder with hot and cool function	•	•	•
Electric horn	•	•	•
Engine shut-off switch	•	•	•
Equipped with reinforced glass windows	•	•	•
Evacuation hammer	•	•	•
Fire extinguisher mounting seat	•	•	•
Footrest	•	•	•
Floor mat	•	•	•
Front window washer (1 point)	•	•	•
Front window washer (2 points) *	0	0	0
Hands-free calling device	•	•	•
Hot and cool box	•	•	•
Intermittent windshield wipers	•	•	•
LED room light	•	•	•
Lower front window one-touch lock (release lever)	•	•	•
Magazine rack	0	0	0
OPG top guard, Level II (ISO 10262 : 1998) compliant	0	0	0
OPG front guard, Level II (ISO 10262 : 1998) compliant	0	0	0
Pilot shut-off lever	•	•	•
Power outlet 12 V	•	•	•
Rain guard (without OPG front guard) **	0	0	0
Rear tray	•	•	•
Retractable seat belt	•	•	•
Rubber radio antenna	•	•	•
ROPS (ISO 12117-2 : 2008) compliant cab	•	•	•
Seat : air suspension seat with heater	•	•	•
Seat adjustment part : backrest, armrest, height and angle, slide forward / back	•	•	•
Seat belt reminder	•	•	•
Smartphone holder	•	•	•
Sunscreen roller type (top window)	•	•	•
Sunscreen roller type (front window)	0	0	0
Tined window glass (right side)	0	0	0
Transparent roof	•	•	•
USB power supply	•	•	•
Wide view wiper	0	0	0
Windows on front, upper and lower can be opened	•	•	•
Window (right side) guard pipe	•	•	-
4 fluid-filled elastic mounts	•	•	•
8 inch monitor	•	•	•
o morrimonico			1

● : Standard equipment O : Optional equipment - : Not applicable

MONITOR SYSTEM	ZX95US-7	ZX95US-7 2-piece	ZX95USB-7
Alarms: overheat, engine warning, engine oil pressure, alternator, minimum fuel level,air filter restriction, work mode, overload, etc	•	•	•
Alarm buzzers: overheat, engine oil pressure, overload, etc	•	•	•
Display of meters: water temperature, hour, fuel rate, clock, etc	•	•	•
Other diaplays: work mode, auto-idle, glow, rearview monitor, operating conditions, etc	•	•	•
35 language selection	•	•	•

LIGHTS	ZX95US-7	ZX95US-7 2-piece	ZX95USB-7
Additional 3 cab roof front LED lights	0	•	0
Boom LED lights (boom x 1, cab front x 1)	•	•	•
3 ambient LED lights (side and rear view camera)	0	0	0

UPPER STRUCTURE	ZX95US-7	ZX95US-7 2-piece	ZX95USB-7
Accumulator	•	•	•
AERIAL ANGLE (270-degree view camera system)	•	•	•
Auxiliary overload relief valve	•	•	•
Batteries 2 x 60 Ah	•	•	•
Fuel level float	•	•	•
Remote swing circle lubrication	•	•	•
Lockable tool box	•	•	•
Side view mirror (left side)	•	•	•
Undercover	•	•	•
1 165 kg counterweight	•	•	•
430 kg additional counterweight	0	•	0
2 way disconnect switch	•	•	•

UNDERCARRIAGE	ZX95US-7	ZX95US-7 2-piece	ZX95USB-7
Angle blade	0	0	0
Blade	•	•	•
Blade float	0	0	0
Reinforced track links with pin seals	•	•	•
Travel motor covers	•	•	•
4 tie down hooks	•	•	•
450 mm grouser shoe	•	•	•
450 mm pad crawler shoe	0	0	0
450 mm rubber shoe	0	0	0
600 mm grouser shoe	0	0	0

FRONT ATTACHMENTS	ZX95US-7	ZX95US-7 2-piece	ZX95USB-7
Assist piping	0	•	0
Dirt seal on all bucket pins	•	•	•
Extra piping	•	•	•
HN bushing	•	•	•
HRV cover	•	•	•
Reinforced resin thrust plate	•	•	•
WC (tungsten-carbide) thermal spraying	•	•	•
2 piece boom	-	•	•
1.62 m arm	-	•	- / O***
2.12 m arm	•	•	•
Quick coupler piping	•	•	•

MISCELLANEOUS	ZX95US-7	ZX95US-7 2-piece	ZX95USB-7
ConSite	0	0	0
Global e-service	•	•	•
Standard tool kit	•	•	•
Theft deterrent system**	•	•	•

Standard and optional equipment may vary by country, so please consult authorized dealer for details.

* Double washer is only when equipped with wide-view wipers.

** Hitachi Construction Machinery cannot be held liable for theft, any system will just minimize the risk of theft.

*** Only when Mono boom is equipped, it is not applicable and when 2 piece boom is equipped, it can be installed as option.

**** Hitachi Construction Machinery cannot be held liable for theft, any system will just minimize the risk of theft.

ENGINE	ZX95US-7
Aftertreatment device	•
Air cleaner double filters	•
Alternator 24 V - 60 A	•
Auto idle system	•
Auto shut-down control	•
Cartridge-type engine oil filter	•
Cartridge-type fuel main filter	•
ConSite OIL (Sensor)	0
"Dry-type air filter with evacuator valve (with air filter restriction indicator)"	•
Electric fuel refilling pump	•
Engine oil drain coupler	•
Fan guard	•
Fuel cooler	•
Fuel pre-filter with water separator	•
Maintenance free pre-cleaner	0
PWR/ECO mode control	•
Radiator reserve tank	•
Radiator, oil cooler with one touch type cleaning interval extension net	0
Radiator, oil cooler with one touch type dust-proof indoor net	•

HYDRAULIC SYSTEM	ZX95US-7
Auxiliary flow adjustment switching	0
Boom anti-drift valve	•
ConSite OIL (Sensor)	0
Extra port for control valve	•
Full-flow filter	•
Hose rupture valve for arm cylinder	•
Hose rupture valve for boom cylinder	•
Hydraulic pilot type control levers	•
Low-temperature starting speed control	•
Main pump pressure and temperature sensor	•
Pilot control shut-off lever with neutral engine start system	•
Pilot filter	•
Suction filter	•
Swing drain filter	•
Swing parking brake	•
Travel parking brake	•
Two-speed travel system	•
Valve for extra piping	•
Variable reliefvalve for breaker and crusher	•
Work mode selector	•

CAB	ZX95US-7
AUX function lever (breaker)	0
AUX function lever (breaker / boom swing assist)	0
Auto control air conditioner	•
Blade lever with two-speed travel switch	•
Bluetooth® integrated radio	•
Cab with laminate glass only for front window	0
Control lever auto-lock	•
Defroster	•
Drink holder with hot and cool function	•
Electric horn	•
Engine shut-off switch	•
Equipped with reinforced glass windows	•
Evacuation hammer	•
Fire extinguisher mounting seat	•
Footrest	•
Floor mat	•
Front window washer (1 points)	•
Front window washer (2 points) *	0
Hands-free calling device	•
Hot and cool box	•
Intermittent windshield wipers	•
LED room light	•
Lower front window one-touch lock (release lever)	•
Magazine rack	0
Pilot shut-off lever	•
Power outlet 12 V	•
Rain guard (without OPG front guard) **	0
Rear tray	•
Retractable seat belt	•
Rubber radio antenna	•
ROPS (ISO 12117-2 : 2008) compliant cab	•
Seat : air suspension seat with heater	•
Seat adjustment part : backrest, armrest, height and angle, slide forward / back	•
Seat belt reminder	•
Smartphone holder	•
Sunscreen roller type (top window)	•
Sunscreen roller type (front window)	0
Tined window glass (right side)	0
Transparent roof	•
USB power supply	•
Wide view wiper	0
Windows on front, upper and lower can be opened	•
Window (right side) guard piping	•
4 fluid-filled elastic mounts	•
8 inch monitor	•
2 speakers	•

MONITOR SYSTEM	ZX95US-7
Alarms:overheat, engine warning, engine oil pressure, alternator, minimum fuel level, hydraulic filter restriction, air filter restriction, work mode, overload, etc	•
Alarm buzzers: overheat, engine oil pressure, overload, etc	•
Display of meters: water temperature, hour, fuel rate, clock, etc	•
Other diaplays:work mode, auto-idle, glow, rearview monitor, operating conditions, etc	•
35 language selection	•

LIGHTS	ZX95US-7
Additional 3 cab roof front LED lights	0
Boom LED lights (boom x 1, cab front x 1)	•
3 ambient LED lights (side and rear view camera)	0

UPPER STRUCTURE	ZX95US-7
AERIAL ANGLE (270-degree view camera system)	•
Auxiliary overload relief valve	•
Batteries 2 x 60Ah	•
Fuel level float	•
Remote swing circle lubrication	•
Lockable tool box	•
Side view mirror (left side)	•
Undercover	•
1 165 kg counterweight	•
430 kg additional counterweight	•
2 way disconnect switch	•

UNDERCARRIAGE	ZX95US-7
Blade	•
Blade float	0
Reinforced track links with pin seals	•
Travel motor covers	•
4 tie down hooks	•
450 mm grouser shoe	•
450 mm pad crawler shoe	0
450 mm rubber shoe	0

FRONT ATTACHMENTS	ZX95US-7
Assist piping	0
Dirt seal on all bucket pins	•
Extra piping	•
HN bushing	•
HRV valve cover	•
Reinforced resin thrust plate	•
WC (tungsten-carbide) thermal spraying	•
5.48 m boom	•
4.04 m arm	•
Quick coupler piping ***	0

MISCELLANEOUS	ZX95US-7
ConSite	0
Global e-service	•
Standard tool kit	•
Theft deterrent system****	•

Standard and optional equipment may vary by country, so please consult authorized dealer for details.

* Double washer is only when equipped with wide-view wipers.

** Rain guard cannot be install when Cab front top guard and cab ceiling tower guard ISO (OPG) Level II conformance (ISO10262: 1998) are installed.

*** Quick coupler piping shall be up to upper structure outlet.

*** Hitachi Construction Machinery cannot be held liable for theft, any system will just minimize the risk of theft.

Prior to operating this machine, including satellite communication system, in a country other than a country of its intended use, it may be necessary	These specifications are subject to change without notice. Illustrations and photos show the standard models, and may or may not include optional
to make modifications to it so that it complies with the local regulatory standards (including safety standards) and legal requirements of that particular country. Please do not export or operate this machine outside the country of its intended use until such compliance has been confirmed. Please contact your Hitachi dealer in case of questions about compliance.	equipment, accessories, and all standard equipment with some differences in colour and features. Before use, read and understand the Operator's Manual for proper operation.

Hitachi Construction Machinery

www.hitachicm.eu