

650TLX


**650
TLX**

HYDRAULIC CRAWLER CRANE

Variation of The Attachment

Line Speed *	Front / Rear Winch	m/min	105
	Third Winch (Optional)		105
Boom Raising Speed*	sec/degree		52 / 0 to 78.0
Swing Speed	min ⁻¹ (rpm)		4.5
Travel Speed High / Low *	km/h		1.7 / 1.2
Gradeability	% (Degree)		30 (17)
Engine Model			ISUZU 6HK1 (Stage III B, Int.Tier 4)
Engine Rated Output Power	kW/min ⁻¹ (ps/rpm)		210 / 1900 (285 / 1900)

Note : Speeds marked with "*" may vary depending on load applied.



**Crane Specification
(Boom Longest Length)**

Boom Length	m	10 to 30.1
Ground Contact Pressure	kPa (kgf/cm ²)	92.4 (0.94) (with 65 t hook)
Overall Operating Weight	t	70.9 (with 65 t hook)

VARIATION

Variation of The Attachment	2
------------------------------------	----------

SPECIFICATIONS

Specifications	4
-----------------------	----------

Crane Specifications	5
-----------------------------	----------

Dimensions and Specifications	5
--------------------------------------	----------

Working Ranges	6
-----------------------	----------

■ Main Boom with Aux. Sheave	6
------------------------------	---

■ Main Boom with Aux. Sheave (2 Sheaves)	6
--	---

■ Aux. Sheave	6
---------------	---

■ Aux. Sheave (2 Sheaves)	6
---------------------------	---

Working Ranges: Without Counter Weight	7
---	----------

■ Main Boom with Aux. Sheave	7
------------------------------	---

■ Main Boom with Aux. Sheave (2 Sheaves)	7
--	---

■ Aux. Sheave	7
---------------	---

■ Aux. Sheave (2 Sheaves)	7
---------------------------	---

Working Ranges: When Jacking Up, Without Counter Weight	8
--	----------

■ Main Boom with Aux. Sheave	8
------------------------------	---

■ Main Boom with Aux. Sheave (2 Sheaves)	8
--	---

Gross Rated Load Table	9
-------------------------------	----------

■ Main Boom with Aux. Sheave	9
------------------------------	---

■ Aux. Sheave	10
---------------	----

■ Main Boom with Aux. Sheave (2 Sheaves)	11
--	----

■ Aux. Sheave (2 Sheaves)	12
---------------------------	----

■ Main Boom with Aux. Sheave (Without Counter Weight)	13
---	----

■ Aux. Sheave (Without Counter Weight)	14
--	----

■ Main Boom with Aux. Sheave (2 Sheaves) (Without Counter Weight)	15
---	----

■ Aux. Sheave (2 Sheaves) (Without Counter Weight)	16
--	----

■ Main Boom with Aux. Sheave (When Jacking Up, Without Counter Weight)	17
--	----

■ Main Boom with Aux. Sheave (2 Sheaves) (When Jacking Up, Without Counter Weight)	18
--	----

TECHNICAL DATA

Weights and Dimensions of Disassembled Units	19
---	-----------

Weights and Dimensions List	19
------------------------------------	-----------

Equipment List	21
-----------------------	-----------

Standard and Optional Equipment	21
--	-----------

Specifications



Engine

Model	ISUZU 6HK1
Type	4-cycle, Water-cooled, Direct injection, Turbo-charged, Diesel engine
Displacement	7.79 liters
Rated Output	210 kW / 1,900 min ⁻¹ (285 ps / 1,900 rpm)
Fuel Tank Capacity	400 liters
Notes	Engine meets Stage III B / Int. Tier 4 of engine exhaust gas emission regulations in USA, Europe, and Japan. Engine rated horsepower is based on international rating formula that includes engine alternator and without fan.



Control

Control System	Main actuators are actuated by main hydraulic system controlled with pilot hydraulic system. Safety devices are securely operated by combined various electronic control with hydraulic system. Working speed can be precisely controlled according to control lever stroke and control dials depending on work.
Control Levers	Designed and positioned based on ergonomics. Arm-chair lever type is standard.
Display Panel Design	8 inches size. Located to check work state easily without disturbing the view of the operator.



Hydraulic System

Hydraulic Oil Tank Capacity	800 liters		
Hydraulic Pump Capacity	Max.	31.4 MPa	
	P1	266 L / min	Front winch, Third winch, Auger, Boom telescoping and Travel
	P2	266 L / min	Rear winch, Auger, Boom hoist and Travel
	P3	152 L / min	Swing, Jack, Crawler sideframe extend-retract and External hydraulic power equipment B
	P4	38 L / min	Pilot control, External hydraulic power equipment A and others.
	P5	38 L / min	
	P6	38 L / min	
	P7	30 L / min	



Winch

Front and Rear Winch				
Winch		Front	Rear	
Rope Diameter		22.4mm	22.4mm	
Rope Winding Length	Standard	175 m	76 m	for Aux. sheave
	Max. (In non-work)	260 m	260 m	
Line Pull	Rated	69 kN	69 kN	
Standard Equipment		Free fall winch with brake controlled by pedal operation.		

Third Winch (Optional)

Rope Diameter	22.4mm	
Rope Winding Length	Standard	170 m
	Max. (In non-work)	260 m (With free fall) 280 m (Without free fall)
Line Pull	Rated	69 kN
Notes	Winch without free fall or free fall winch with brake controlled by pedal operation.	



Swing System

Consisted of hydraulic motor with reduction gear and multi-disc brakes and a swing bearing which has inner tooth.



Counter Weight

Counter Weight (Without self assembly unit)	Total Weight	14.0 ton
	3.0 ton Base Weight	1 piece
	2.7 ton Right Weight	2 pieces
	2.8 ton Left Weight	2 pieces
Counter Weight (With self assembly unit)	Total Weight	13.6 ton
	2.6 ton Base Weight	1 piece
	2.7 ton Right Weight	2 pieces
	2.8 ton Left Weight	2 pieces



Carbody

Welded steel construction with crawler sideframe extend-retract cylinders.




Crawler Sideframe

Frame	Welded steel box construction, and can be retracted.	
Shoe	Cast iron 760 mm width shoe each side.	
Upper Roller	2 pieces each side.	
Lower Roller	10 pieces each side.	
	Forging heat treated steel with double flange type. 2 plane bearing with floating seal for lifetime lubrication.	
Travel Device	1 piece each side.	
	Hydraulic travel device (Hydraulic motor and reducer)	
	Travel speed (Gradability : 30%)	High : 1.7 km/h Low : 1.2 km/h

Crane Specifications

Dimensions and Specifications



Crane Specifications

Max. Lifting Load × Working Radius	t × m	65×3.0
Basic Boom Length	m	10.0
Max. Boom Length	m	30.1
Ground Contact Pressure	kPa (kgf/cm ²)	92.4 (0.91) (w / 65 t Hook)
Overall Operating Weight	t	70.9 (w / 65 t Hook)


NOTE : Data is expressed in SI units followed by conventional units in ().

Hook Weight


65 t	800 kg
30 t	520 kg
7 t	105 kg

Working Ranges


■ Main Boom with Aux. Sheave




■ Aux. Sheave



■ Main Boom with Aux. Sheave (2 Sheaves)




■ Aux. Sheave (2 Sheaves)




Working Ranges: Without Counter Weight


Main Boom with Aux. Sheave




Aux. Sheave



Main Boom with Aux. Sheave (2 Sheaves)



Aux. Sheave (2 Sheaves)





Working Ranges: When Jacking Up, Without Counter Weight



■ Main Boom with Aux. Sheave

■ Main Boom with Aux. Sheave (2 Sheaves)

65 t Hook 30 t Hook



65 t Hook 30 t Hook



Gross Rated Load Table

Main Boom with Aux. Sheave



Unit: ton

Working Radius(m)	Boom Length (m)				Working Radius(m)
	10.0	16.7	23.4	30.1	
2	65.0				2
2.5	65.0				2.5
3	65.0	32.0			3
3.5	55.0	32.0			3.5
4	48.0	32.0	26.0		4
4.5	41.5	32.0	26.0		4.5
5	37.0	30.5	26.0	16.0	5
5.5	34.0	28.8	25.0	16.0	5.5
6	32.5	26.5	23.0	16.0	6
7	26.3	23.0	20.2	16.0	7
8	7.7m x	19.7	17.8	15.0	8
9	22.5t	16.7	15.5	13.4	9
10		14.3	13.5	12.0	10
12		10.5	10.3	9.9	12
14		13.0m x	7.9	8.0	14
16		9.1t	6.0	6.5	16
18			4.6	5.2	18
20			19.0m x	4.1	20
22			4.1t	3.1	22
24				2.3	24
26				25.0m x	26
28				2.0t	28

1. The maximum rated loads as above are the value of the stationary loads on a firm and level surface, are not more than 78% of minimum tipping loads, and 1.15 or more as specified in mobile crane structure specifications.
2. To calculate the maximum load that can actually be lifted, deduct mass of all lifting accessories, such as a hook, from figures shown above.
3. Capacities surrounded by bold lines are based on factors other than those which would cause a tipping condition.
4. Working radius is the horizontal distance from the slewing center to the center of gravity of a lifted load.
5. 14 ton counter weight is required for all capacities on this chart.
6. Correlation between the number of reeved lines, maximum rated loads, hook mass are shown in the table below.

Hook Capacity	Hook Mass (ton)	Maximum Rated Loads (ton)							
		10 falls	8 falls	6 falls	5 falls	4 falls	3 falls	2 falls	1 fall
65t	0.80	65	56	42	-	28	-	14	-
30t	0.52	-	-	-	30	28	21	14	-
7t	0.11	-	-	-	-	-	-	-	7

■ Aux. Sheave



Unit: ton

Working Radius(m)	Boom Length (m)				Working Radius(m)
	10.0	16.7	23.4	30.1	
2.5	7.0				2.5
3	7.0				3
3.5	7.0	7.0			3.5
4	7.0	7.0			4
4.5	7.0	7.0	7.0		4.5
5	7.0	7.0	7.0		5
5.5	7.0	7.0	7.0	7.0	5.5
6	7.0	7.0	7.0	7.0	6
7	7.0	7.0	7.0	7.0	7
8	7.7m x 7.0t	7.0	7.0	7.0	8
9		7.0	7.0	7.0	9
10		7.0	7.0	7.0	10
12		7.0	7.0	7.0	12
14		13.0m x 7.0t	7.0	7.0	14
16			6.0	6.5	16
18			4.6	5.2	18
20			19.0m x 4.1t	4.1	20
22				3.1	22
24				2.3	24
26				25.0m x 2.0t	26
28					28

1. The maximum rated loads as above are the value of the stationary loads on a firm and level surface, are not more than 78% of minimum tipping loads, and 1.15 or more as specified in mobile crane structure specifications.
2. To calculate the maximum load that can actually be lifted, deduct mass of all lifting accessories, such as a hook, from figures shown above.
3. Capacities surrounded by bold lines are based on factors other than those which would cause a tipping condition.
4. Working radius is the horizontal distance from the slewing center to the center of gravity of a lifted load.
5. 14 ton counter weight is required for all capacities on this chart.
6. Hook mass are shown in the table below.

Hook Capacity	Hook Mass (ton)
7t	0.11

■ Main Boom with Aux. Sheave (2 Sheaves)



Unit: ton

Working Radius(m)	Boom Length (m)				Working Radius(m)
	10.0	16.7	23.4	30.1	
2	65.0				2
2.5	65.0				2.5
3	65.0	31.9			3
3.5	54.9	31.9			3.5
4	47.9	31.9	25.9		4
4.5	41.4	31.9	25.9		4.5
5	36.9	30.4	25.9	15.9	5
5.5	33.9	28.7	24.9	15.9	5.5
6	32.4	26.4	22.9	15.9	6
7	26.2	22.9	20.1	15.9	7
8	7.7m x	19.6	17.7	14.9	8
9	22.4t	16.6	15.4	13.3	9
10		14.2	13.4	11.9	10
12		10.4	10.2	9.8	12
14		13.0m x	7.8	7.9	14
16		9.0t	5.9	6.4	16
18			4.5	5.1	18
20			19.0m x	4.0	20
22			4.0t	3.0	22
24				2.2	24
26				25.0m x	26
28				1.9t	28

1. The maximum rated loads as above are the value of the stationary loads on a firm and level surface, are not more than 78% of minimum tipping loads, and 1.15 or more as specified in mobile crane structure specifications.
2. To calculate the maximum load that can actually be lifted, deduct mass of all lifting accessories, such as a hook, from figures shown above.
3. Capacities surrounded by bold lines are based on factors other than those which would cause a tipping condition.
4. Working radius is the horizontal distance from the slewing center to the center of gravity of a lifted load.
5. 14 ton counter weight is required for all capacities on this chart.
6. Correlation between the number of reeved lines, maximum rated loads, hook mass are shown in the table below.

Hook Capacity	Hook Mass (ton)	Maximum Rated Loads (ton)							
		10 falls	8 falls	6 falls	5 falls	4 falls	3 falls	2 falls	1 fall
65t	0.80	65	56	42	-	28	-	14	-
30t	0.52	-	-	-	30	28	21	14	-
7t	0.11	-	-	-	-	-	-	-	7

■ Aux. Sheave (2 Sheaves)



Unit: ton

Working Radius(m)	Boom Length (m)				Working Radius(m)
	10.0	16.7	23.4	30.1	
2.5	7.0				2.5
3	7.0				3
3.5	7.0	7.0			3.5
4	7.0	7.0			4
4.5	7.0	7.0	7.0		4.5
5	7.0	7.0	7.0		5
5.5	7.0	7.0	7.0	7.0	5.5
6	7.0	7.0	7.0	7.0	6
7	7.0	7.0	7.0	7.0	7
8	7.7m x 7.0t	7.0	7.0	7.0	8
9		7.0	7.0	7.0	9
10		7.0	7.0	7.0	10
12		7.0	7.0	7.0	12
14		13.0m x 7.0t	7.0	7.0	14
16			5.9	6.4	16
18			4.5	5.1	18
20			19.0m x 4.0t	4.0	20
22				3.0	22
24				2.2	24
26				25.0m x 1.9t	26
28					28

1. The maximum rated loads as above are the value of the stationary loads on a firm and level surface, are not more than 78% of minimum tipping loads, and 1.15 or more as specified in mobile crane structure specifications.
2. To calculate the maximum load that can actually be lifted, deduct mass of all lifting accessories, such as a hook, from figures shown above.
3. Capacities surrounded by bold lines are based on factors other than those which would cause a tipping condition.
4. Working radius is the horizontal distance from the slewing center to the center of gravity of a lifted load.
5. 14 ton counter weight is required for all capacities on this chart.
6. Hook mass are shown in the table below.

Hook Capacity	Hook Mass (ton)
7t	0.11

■ Main Boom with Aux. Sheave (Without Counter Weight)



Unit: ton

Working Radius(m)	Boom Length (m)		Working Radius(m)
	10.0	16.7	
2	26.0		2
2.5	26.0		2.5
3	26.0	19.0	3
3.5	26.0	19.0	3.5
4	26.0	19.0	4
4.5	26.0	19.0	4.5
5	21.8	19.0	5
5.5	18.0	16.5	5.5
6	15.3	14.0	6
7	11.4	10.5	7
8	7.7m x 9.5t	8.2	8
9		6.5	9
10		5.3	10
12		3.6	12
14		13.0m x 3.0t	14
16			16

1. The maximum rated loads as above are the value of the stationary loads on a firm and level surface, are not more than 78% of minimum tipping loads, and 1.15 or more as specified in mobile crane structure specifications.
2. To calculate the maximum load that can actually be lifted, deduct mass of all lifting accessories, such as a hook, from figures shown above.
3. Working radius is the horizontal distance from the slewing center to the center of gravity of a lifted load.
4. Correlation between the number of reeved lines, maximum rated loads, hook mass are shown in the table below.

Hook Capacity	Hook Mass (ton)	Maximum Rated Loads (ton)			
		4 falls	3 falls	2 falls	1 fall
65t	0.80	28	-	14	-
30t	0.52	28	21	14	-
7t	0.11	-	-	-	7

■ Aux. Sheave (Without Counter Weight)



Unit: ton

Working Radius(m)	Boom Length (m)		Working Radius(m)
	10.0	16.7	
2.5	7.0		2.5
3	7.0		3
3.5	7.0	7.0	3.5
4	7.0	7.0	4
4.5	7.0	7.0	4.5
5	7.0	7.0	5
5.5	7.0	7.0	5.5
6	7.0	7.0	6
7	7.0	7.0	7
8	7.7m x	7.0	8
9	7.0t	6.5	9
10		5.3	10
12		3.6	12
14		13.0m x	14
16		3.0t	16

1. The maximum rated loads as above are the value of the stationary loads on a firm and level surface, are not more than 78% of minimum tipping loads, and 1.15 or more as specified in mobile crane structure specifications.
2. To calculate the maximum load that can actually be lifted, deduct mass of all lifting accessories, such as a hook, from figures shown above.
3. Capacities surrounded by bold lines are based on factors other than those which would cause a tipping condition.
4. Working radius is the horizontal distance from the slewing center to the center of gravity of a lifted load.
5. Hook mass are shown in the table below.

Hook Capacity	Hook Mass (ton)
7t	0.11

■ Main Boom with Aux. Sheave (2 Sheaves) (Without Counter Weight)



Unit: ton

Working Radius(m)	Boom Length (m)		Working Radius(m)
	10.0	16.7	
2	26.0		2
2.5	26.0		2.5
3	26.0	18.9	3
3.5	26.0	18.9	3.5
4	26.0	18.9	4
4.5	26.0	18.9	4.5
5	21.7	18.9	5
5.5	17.9	16.4	5.5
6	15.2	13.9	6
7	11.3	10.4	7
8	7.7m x 9.4t	8.1	8
9		6.4	9
10		5.2	10
12		3.5	12
14		13.0m x 2.9t	14
16			16

1. The maximum rated loads as above are the value of the stationary loads on a firm and level surface, are not more than 78% of minimum tipping loads, and 1.15 or more as specified in mobile crane structure specifications.
2. To calculate the maximum load that can actually be lifted, deduct mass of all lifting accessories, such as a hook, from figures shown above.
3. Working radius is the horizontal distance from the slewing center to the center of gravity of a lifted load.
4. Correlation between the number of reeved lines, maximum rated loads, hook mass are shown in the table below.

Hook Capacity	Hook Mass (ton)	Maximum Rated Loads (ton)			
		4 falls	3 falls	2 falls	1 fall
65t	0.80	28	-	14	-
30t	0.52	28	21	14	-
7t	0.11	-	-	-	7

■ Aux. Sheave (2 Sheaves) (Without Counter Weight)



Unit: ton

Working Radius(m)	Boom Length (m)		Working Radius(m)
	10.0	16.7	
2.5	7.0		2.5
3	7.0		3
3.5	7.0	7.0	3.5
4	7.0	7.0	4
4.5	7.0	7.0	4.5
5	7.0	7.0	5
5.5	7.0	7.0	5.5
6	7.0	7.0	6
7	7.0	7.0	7
8	7.7m x	7.0	8
9	7.0t	6.4	9
10		5.2	10
12		3.5	12
14		13.0m x	14
16		2.9t	16

1. The maximum rated loads as above are the value of the stationary loads on a firm and level surface, are not more than 78% of minimum tipping loads, and 1.15 or more as specified in mobile crane structure specifications.
2. To calculate the maximum load that can actually be lifted, deduct mass of all lifting accessories, such as a hook, from figures shown above.
3. Capacities surrounded by bold lines are based on factors other than those which would cause a tipping condition.
4. Working radius is the horizontal distance from the slewing center to the center of gravity of a lifted load.
5. Hook mass are shown in the table below.

Hook Capacity	Hook Mass (ton)
7t	0.11

■ Main Boom with Aux. Sheave (When Jacking Up, Without Counter Weight)



Unit: ton

Working Radius(m)	Boom Length (m)
	10.0
2	9.5
2.5	9.5
3	9.5
3.5	9.5
4	9.5
4.5	9.5
5	9.5
5.5	7.5
6	6.0
6.5	5.0

1. This gross rated load table is for the crawler side frame self removal/installation.
Do not use this for other than self removal/installation.
2. The maximum rated loads as above are the value of the stationary loads on a firm and level surface, are not more than 78% of minimum tipping loads, and 1.15 or more as specified in mobile crane structure specifications.
3. To calculate the maximum load that can actually be lifted, deduct mass of all lifting accessories, such as a hook, from figures shown above.
4. Working radius is the horizontal distance from the slewing center to the center of gravity of a lifted load.
5. Correlation between the number of reeved lines, maximum rated loads, hook mass are shown in the table below.

Hook Capacity	Hook Mass (ton)	Maximum Rated Loads (ton)	
		2 falls	1 fall
65t	0.80	14	-
30t	0.52	14	-
7t	0.11	-	7

■ Main Boom with Aux. Sheave (2 Sheaves) (When Jacking Up, Without Counter Weight)



Unit: ton

Working Radius(m)	Boom Length (m)
	10.0
2	9.5
2.5	9.5
3	9.5
3.5	9.5
4	9.5
4.5	9.5
5	9.5
5.5	7.4
6	5.9
6.5	4.9

1. This gross rated load table is for the crawler side frame self removal/installation.
Do not use this for other than self removal/installation.
2. The maximum rated loads as above are the value of the stationary loads on a firm and level surface, are not more than 78% of minimum tipping loads, and 1.15 or more as specified in mobile crane structure specifications.
3. To calculate the maximum load that can actually be lifted, deduct mass of all lifting accessories, such as a hook, from figures shown above.
4. Working radius is the horizontal distance from the slewing center to the center of gravity of a lifted load.
5. Correlation between the number of reeved lines, maximum rated loads, hook mass are shown in the table below.

Hook Capacity	Hook Mass (ton)	Maximum Rated Loads (ton)	
		2 falls	1 fall
65t	0.80	14	-
30t	0.52	14	-
7t	0.11	-	7








Weights and Dimensions of Disassembled Units

Weights and Dimensions List

Comply with the regulations when transporting.










"Qty" indicates the number of the fully-equipped item and "Weight" indicates the mass of each unit.

Weights and Dimensions of Disassembled Units

Description	Qty	Dimensions (mm)	Weight (kg)
Base Crane with: Aux. Sheave, Boom Front Winch Wire Rope Rear Winch Wire Rope Crawlers 65 t Hook, 7 t Hook Auxiliary Weight	1		56800 (57600)
Base Crane with: Crawlers Boom Hoist Cylinder Without: Wire Rope Auxiliary Weight	1		42600 (44600)
Base Crane with: Boom Without: Aux. Sheave Wire Rope Hook Auxiliary Weight	1		38800 (40800)
Base Crane with: Boom Hoist Cylinder Without: Wire Rope Auxiliary Weight	1		27900 (29900)
Base Crane with: Boom Folding Type Jack Beam Without: Aux. Sheave Wire Rope Hook Auxiliary Weight	1		41600 (43600)
Base Crane with: Boom Hoist Cylinder Folding Type Jack Beam Without: Wire Rope Auxiliary Weight	1		30700 (32700)
Crawler	2		7390

* The value within () shows the case of the third winch attached. With the third winch, auxiliary weight is not attached.

Weights and Dimensions of Disassembled Units

Description	Qty	Dimensions (mm)	Weight (kg)
Counter Weight (R)	2		2730
Counter Weight (L)	2		2780
Counter Weight (Base)	1	 * () is attached the self assembly unit (OPT).	2960 (2570)
Boom (with Aux. Sheave)	1		11200
Folding Type Jack Beam	2		1400
Jack Beam	2		1410
65 t Hook	1		800
30 t Hook	1		520
7 t Hook	1		105

Equipment List

Standard and Optional Equipment

○ : Standard ● : Optional

Item		
Lower Structure	760 mm Crawler Shoe	○
	Crawler Extension/Retraction System	○
	Steps	○
	Folding Type Jack Beam ^{*1}	●
	Jack Beam ^{*1}	●
	Shoe Tension Unit (Hydraulic)	●
Upper Structure	Cab Up/Down Catwalk	○
	Upper House Handrails (For Catwalk)	○
	Under Cover (Bed Lower Surface)	○
	Working Light (× 2)	○
	Back Mirror (Left and Right)	○
	Drum Flange Cover	○
	Winch Rope Retainer (Front Winch)	●
	Winch Rope Retainer (Rear Winch)	○
	Winch Rope Retainer (Third Winch)	●
	Catwalk (Folding Type, Left and Right)	●
	Electric Fuel Pump	●
	Handrail (Folding Type)	●
	Front, Rear Winch (φ22.4mm with Free Fall, Brake Mode Select Switch)	○
	Third Winch (φ22.4mm without Free Fall, with Guide Sheave and Winch Drum Lock, and Rope not Included)	●
	Third Winch (φ22.4mm with Free Fall, Guide Sheave and Winch Drum Lock, and Rope not Included)	●
Cab	Standard Counter Weight (2990mm Width)	○
	Counter Weight with Self Assembly Unit (Counter Weight 3800mm Width)	●
	Air Conditioner	○
	Sunvisor	○
	Sunshade	○
	Wiper with Washer (Front Window, Cab Roof Window)	○
	Microphone & Loud-speaker	○
	AM / FM Radio (With Clock)	○
	Room Lamp	○
	Cup Holder	○
	24 V Power Socket (× 2)	○
	Floor Carpet	○
	Level Gauge (In Cab)	○
	Arm Chair Lever	○
	Accelerator Grip	○
	Accelerator Pedal (Right Side)	●
	Drum Rotation Sensor (Front/Rear)	○
	Speed Control Dial (Boom Hoist/Swing)	○
	Boom Hoist Operation Pedal	○
	Boom Hoist Operation Lever (Third Winch Lever is Replaced Forward)	●
	Fire Extinguisher (ABC No.4)	●
	Fan	●
	Life Hammer	○

*1 Jack beam and folding type jack beam cannot be attached at the same time.

○ : Standard ● : Optional

Item		
Attachment	4-Section Telescopic Boom (10 to 30.1m)	○
	Boom Transportation Mount	●
	Boom Assembly/Disassembly Transport Mount	●
	Boom Foot Pin Assembly/Disassembly Jig and Tool	●
	Tool Box for Boom Foot Pin Assembly/Disassembly Jig	●
	Aux. Sheave (1 Sheave) [Aux. Sheave and Anti-two Block]	○
	Aux. Sheave (2 Sheaves)	●
	65 t Hook (5 Sheaves)	○
	30 t Hook (3 Sheaves)	●
Wire rope	7t Hook (Light Type with Lock (105kg))	○
	* It may not fall by its own weight depends on the boom length.	○
	Front Winch (φ 22.4) XP IWRC6XWS (31)	○
	Rear Winch (φ 22.4) XP IWRC6XWS (31)	○
Safety Device	Third Winch (φ 22.4) XP IWRC6XWS (31)	●
	Moment Limiter	○
	3 Color Percentage Indicator Light	○
	Mode Select Switch (Crane/Excavation)	○
	Gate Lock Lever	○
	Individual Operation Lever Lock (Front, Rear, Boom Hoist, Travel)	○
	Winch Drum Lock (Front and Rear)	○
	Swing Lock	○
	Swing Alarm	○
	Travel Alarm	○
	Auto Slowdown (Slow Stop)	○
	Warning Alarm	○
	Engine Start Interlock System	○
	Emergency Engine Stop Switch (In Cab)	○
	Lifting Height Indication Device	○
	Swing Neutral Free/Brake Selection Switch	○
	Anti-two Block	○
	Swing Restriction Unit	●
	Drum and Rear View Monitor System (× 3)	●
Common parts	Cab Roof Window Guard	●
	Remote Sensing (Mobile Communication Terminal, Data Logging Device)	○
	Without Counter Weight (Reduced Counter Weight) Specification	○
	Hydraulic Power Outlet for Auger (Including the boom side piping, maximum pressure: 31.4MPa, maximum flow rate: 520L/min)	●
	External Hydraulic Power Outlet A (Maximum Pressure: 13.7MPa, Maximum Flow Rate: 38L/min)	●
	External Hydraulic Power Outlet B (Maximum Pressure: 27.4MPa, Maximum Flow Rate: 150L/min)	●
	Auger Speed Selector Panel (On the Right Side of the Cab)	●
	Sling Ropes for Disassembly and Assembly (for Counter Weights, Crawlers, Boom)	●
	Boom Stanchion	●
	Reeving Winch Cum Hydraulic Tagline (6 x Fi (29) φ10mm x 55m)	● ^{*2}
	Tool Box (On the Front of the Right Bed)	○
	Additional Fuel Filter (Triple Filter)	●
Other	Additional Spare Parts (Hydraulic Oil Filter)	●
	Additional Tools (Large Hammer, Crowbar, Chisel)	●
	Standard Supplied Tools	○
	Special Tools (When Hydraulic Power Outlet for Auger is Attached)	●
Other	Standard Spare Parts	○

*2 Reeving Winch Cum Hydraulic Tagline

(Maximum line pull: 1.4 kN (150 kgf) for hydraulic tagline / 2.9 kN (300 kgf) for reeving winch)

Handwriting practice lines consisting of 20 horizontal dashed lines.

- We are constantly improving our products and therefore reserve the right to change designs and specifications without notice.
- Units in this specification are shown under International System of Units; the figures in parenthesis are under Gravitational System of Units as old one.

Sumitomo Heavy Industries Construction Cranes Co., Ltd.

9-3, Higashi-Ueno 6-chome, Taito-ku, Tokyo 110-0015, Japan
Phone: 81-3-3845-1387 Facsimile: 81-3-3845-1394

<http://www.hsc-cranes.com>